



EDA126-01-2 TEST
DASH NO. APPLICATION

UNLESS OTHERWISE SPECIFIED:
1. MARK PER BPS FW 4050
2. BREAK ALL SHARP EDGES
.015 x 45° OR .015 R
3. TOLERANCE PER BPS FW 4018
4. SAFETY Factor PER BPS FW 4043
5. DIMENSIONAL LIMITS APPLY
AFTER PLATING

APPLICABLE DOCUMENTS:
ABBREVIATIONS PER MIL-STD-12
DIMENSIONAL AND TOLERANCING
PER USAS Y14.5
ELECTRICAL SYMBOLS
PER USAS Y32.2
ELECTRICAL REF DESIGNATIONS
PER USAS Y32.16

FINISH
SPEC
UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
DECIMALS ANGLES
XXX ± .000 ± .000
XX ± .000 ± .000
X ± .1 ± .000

SURFACE ROUGHNESS PER USAS B46.1
125 MACHINED SURFACES
EXCEPT AS NOTED

CONTRACT NUMBER DAAJ01-73-C-0248
DRAWN J. ALCON 1-25-74
CHECKED

STRESS
WEIGHTS
GROUP ENGR K. WILSON 265-5874
DER

MET. DESIGN

PROJECT 02/25/74

CUSTOMER

CODE IDENT NO. D 97499
DWC NO. T101968
SCALE 1/1 SHEET 1 OF 1

BELL
HELICOPTER COMPANY
POST OFFICE BOX 448 - FORT WORTH, TEXAS 76101 A SUBSIDIARY OF THE BELL GROUP OF COMPANIES

TITLE
SLEEVE-SUPPORT, COVER

744501

RELEASED FOR PROD
DATE: 6/12/09 INT: GUB

SHOP COPY

RB-T101968

REVISIONS			
LTR	DESCRIPTION	DATE	APPROVED

NOTES:

1. T101968 IS USED TO SUPPORT 214-040-212
COVER WHILE REMOVING 214-040-205 GEAR.